

SK-WP / SK-WPZ Series

STAINLESS STEEL, WASHDOWN DIGITAL SCALES

Ideal for harsh environment applications, such as food processing, foodservice, chemical and outdoor use

Resolution
Up to 5,000
graduations!

Large 1" LCD
Display



lb/kg/oz Mode Selection
(varies with model)

Portable Battery Power
(batteries not included)

National Sanitation Foundation (NSF) Certified

Features

- 2 Year Warranty
- Low Battery Indication with Auto Power Off (5 min.) to preserve battery life
- AC Adapter (option)
- Large, removable stainless steel pan (9" x 7.5")
- Re-Zero (tare) Function
- Temperature Compensated
- Full Scale Pushbutton Tare/Zero

SK-WP Series	Metric Mode		Lb Mode	
	Capacity	Resolution	Capacity	Resolution
SK-1000WP	1000 g	0.5 g	2.2 lb	0.001 lb
SK-2000WP	2000 g	1 g	4.4 lb	0.002 lb
SK-5000WP	5000 g	2 g	11 lb	0.005 lb
SK-5001WP	5000g	1g	-	-
SK-10KWP	10 kg	0.005 kg	22 lb	0.01 lb
SK-20KWP	20 kg	0.01 kg	44 lb	0.02 lb

SK-WPZ Series	Metric Mode		Lb Mode		Dec. oz Mode		Fract. oz Mode	
	Capacity	Resolution	Capacity	Resolution	Capacity	Resolution	Capacity	Resolution
SK-2000WPZ	2000 g	1 g	4.4 lb	0.002 lb	4 lb, 6 oz	0.1 oz	4lb, 6oz	1/16 oz
SK-5000WPZ	5000 g	2 g	11 lb	0.005 lb	11 lb	0.1 oz	11 lb	1/8 oz
SK-20KWPZ	20 kg	0.01 kg	44 lb	0.02 lb	44 lb	1 oz	44 lb	1 oz

Fax-on-Demand

(800) 726-7099, Press 2 / (408) 263-2278

Document #1010

www.andweighing.com

last saved:10/29/02



1555 McCandless Drive
Milpitas, CA 95035, USA
Toll Free: (800) 726-7099
Phone: (408) 263-5333
Fax: (408) 263-0119

SK-WP / SK-WPZ Series Specifications

	SK-1000WP	SK-2000WP	SK-5000WP	SK-5001WP	SK-10KWP
Grams (g)	1000 x 0.5g	2000 x 1g	5000 x 2g	5000 x 1g	-
Kilogram (kg)	-	-	-	-	10 x 0.005kg
Pounds (lb)	2.2 x 0.001lb	4.4 x 0.002lb	11 x 0.005lb	-	22 x 0.01lb
Linearity	± 1g	± 2g	± 4g	± 2g	± 0.01kg
Repeatability/ Std. Deviation	0.5g	1g	2g	1g	0.005kg

	SK-20KWP	SK-2000WPZ	SK-5000WPZ	SK-20KWPZ
Grams (g)	-	2000 x 1g	5000 x 2g	-
Kilogram (kg)	20 x 0.01kg	-	-	20 x 0.01kg
Pound (lb)	44 x 0.02lb	4.4 x 0.002lb	11 x 0.005lb	44 x 0.02lb
Lb/oz fractional ounce	-	4lb, 6oz x 1/16 oz	11 lb x 1/8 oz	44 lb x 1 oz
Lb/oz decimal ounce	-	4 lb, 6 oz x 0.1 oz	11 lb x 0.1 oz	44 lb x 1 oz
Linearity	± 0.02kg	± 2g	± 4g	± 0.02kg
Repeatability/ Std Deviation	0.01kg	1g	2g	0.01kg

All Models	
Display	25mm/ 1 inch, 7 segment LCD
Platform Size	232 (W) x 192 (D) mm / 9.1 (W) x 7.5 (D) inches
Dimensions	150 (H) x 266 (W) x 280 (D) mm / 5.75 (H) x 10.5 (W) x 11 (D) inches
Power	6 'D' size batteries (not included) or FV-05 AC adapter (option)
Battery Life	Approx. 600 hours (manganese type), 1200 hours (alkaline at 20° C / 68° F)
Operating Temp.	-10°C~40°C / 14°F~104°F HR less than 85%
Weight	Approx. 2.9 kg. / 6.4 lb

Specifications are subject to change without notice.

Options:

- FV-05 AC Adapter (110VAC) – power transformer is not waterproof
- FV-06 AC Adapter (220VAC) – power transformer is not waterproof

**NTEP APPROVAL CofC#98-086A2
(except SK-5001WP and WPZ models)**

Fax-on-Demand

(800) 726-7099, Press 2 / (408) 263-2278

Document #1010

www.andweighing.com

last saved:10/29/02



1555 McCandless Drive
Milpitas, CA 95035, USA
Toll Free: (800) 726-7099
Phone: (408) 263-5333
Fax: (408) 263-0119